

Example

Cuelist - Go back

by:	Gregory Haynes, Jul. 2017
published:	http://forum.avolites.com/viewtopic.php?f=20&t=5274
description:	makes a specific cuelist go back
remarks:	snippet which explains CueLists.GoBack(Handle handle)

[cuelist](#), [go back](#), [handle](#), [location](#)

functions

- [CueLists.GoBack](#)

Code

- by location:

```
<step>CueLists.GoBack("Location=Playbacks,2,1")</step>
```

- by usernumber:

```
<step>CueLists.GoBack(userNumber:1)</step>
```

- file with various cuelists referred:

gobackmacros.xml

Explanation

This explains the functional steps within the sequence. For all the other XML details please refer to [Formats and syntax](#)

This simply calls the function `CueLists.GoBack()` with a designated handle as argument. The handle "Location=Playbacks,2,1" translates to 'Playbacks, page 2, 1st playback' - this is the 'real' fader playbacks (see [Identifiers](#)). *tested - S. Beutel*

How to use it

This is an example oneliner - you need to pack it into a macro file before you can use it in Titan. Example to be used in your own macros.

From:

<https://www.avosupport.de/wiki/> - **AVOSUPPORT**

Permanent link:

<https://www.avosupport.de/wiki/macros/example/cuelistgoback>

Last update: **2021/07/19 14:45**

