

# Cuelist Go back

|                     |   |
|---------------------|---|
| <b>by:</b>          | Gregory Haynes, Jul. 2017   |
| <b>published:</b>   | <a href="http://forum.avolites.com/viewtopic.php?f=20&amp;t=5274">http://forum.avolites.com/viewtopic.php?f=20&amp;t=5274</a> |
| <b>description:</b> | makes a specific cuelist go back  |
| <b>remarks:</b>     | snippet which explains CueLists.GoBack(Handle handle)   |

## functions

- [CueLists.GoBack](#)

## Code

```
<step>CueLists.GoBack("Location=Playbacks,2,1")</step>
```

## Explanation

This explains the functional steps within the sequence. For all the other XML details please refer to [Formats and syntax](#)

This simply calls the function `CueLists.GoBack()` with a designated handle as argument. The handle "Location=Playbacks,2,1" translates to 'Playbacks, page 2, 1st playback' - this is the 'real' fader playbacks (see [Identifiers](#)). *tested - S. Beutel*

## How to use it

This is an example oneliner - you need to pack it into a macro file before you can use it in Titan. Example to be used in your own macros.

From:  
<https://avosupport.de/wiki/> - **AVOSUPPORT**

Permanent link:  
<https://avosupport.de/wiki/macros/example/cuelistgoback?rev=1511128785>

Last update: **2017/11/19 21:59**

