

Example

# Delete Group X

<b>by:</b>	Sebastian Beutel
<b>published:</b>	November 2018
<b>description:</b>	deletes a designated group

[delete](#), [group](#), [handle](#)

## functions

- [Handles.SetSourceHandleFromHandle](#)
- [Handles.ConfirmDelete](#)

## Code

[DeleteGroup20.xml](#)

```
<?xml version="1.0" encoding="utf-8"?>
<avolites.macros>
  <macro id="SB.DeleteGroupUn20" name="Delete Group 20">
    <sequence>
      <step>Handles.SetSourceHandleFromHandle("groupHandleUN=20")</step>
      <step>Handles.ConfirmDelete()</step>
    </sequence>
  </macro>
</avolites.macros>
```

## Explanation

This explains the functional steps within the sequence. For all the other XML details please refer to [Formats and syntax](#)

- `Handles.SetSourceHandleFromHandle("groupHandleUN=20")` marks the group with usernumber 20 as `sourceHandle` for the next operation
- `Handles.ConfirmDelete()` deletes the previously selected handle (the group UN20)

## How to use it

- [make this macro available](#)
- while it may be not that interesting to delete a group by individual macro, this is an example how items can be deleted in general - and maybe this is useful in another context

From:

<https://avosupport.de/wiki/> - **AVOSUPPORT**

Permanent link:

<https://avosupport.de/wiki/macros/example/deletegroup>

Last update: **2018/12/23 15:54**

