

Example

Delete Playback

by:	Lucas Wx, April 2018
published:	https://www.facebook.com/groups/Avolites/permalink/1215020168630215/
description:	Deletes a playback.

[delete](#), [playback](#)

functions

- [Handles.SetSourceHandleFromHandle](#)
- [Handles.GetHandle](#)
- [Handles.ConfirmDelete](#)

Code

```
<?xml version="1.0" encoding="utf-8"?>
<avolites.macros xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:noNamespaceSchemaLocation="Avolites.Menus.xsd">
  <macro id="" name="" >
    <sequence>
      <step
pause="0.01">Handles.SetSourceHandleFromHandle(Handles.GetHandle("Playbacks"
,x,x))</step>
      <step pause="0.01">Handles.ConfirmDelete()</step>
    </sequence>
  </macro>
</avolites.macros>
```

Explanation

This explains the functional steps within the sequence. For all the other XML details please refer to [Formats and syntax](#)

- `Handles.SetSourceHandleFromHandle(Handles.GetHandle("Playbacks",x,x))` points `Handles.SourceHandle` to a particular playback
- `Handles.ConfirmDelete()` deletes this handle

How to use it

- [make this macro available](#)
- this is not fully functional - you need to define the exact handle

From:
<https://avosupport.de/wiki/> - **AVOSUPPORT**

Permanent link:
<https://avosupport.de/wiki/macros/example/deleteplayback?rev=1537100269>

Last update: **2018/09/16 12:17**

