

Example

# Fire/Release Playbacks from Usernumber

<b>by:</b>	Peter Budd
<b>published:</b>	October 2017
<b>description:</b>	Fire/Release some Playbacks.
<b>remarks:</b>	This is also an example of the use of <a href="#">userNumber</a> .

## functions

- [Playbacks.ReleasePlayback](#)
- [FirePlaybackAtLevel](#)

## affected properties

- [Playbacks.MasterReleaseTime](#)

## Code

[firerelaseplaybacks.xml](#)

```
<?xml version="1.0" encoding="utf-8"?>
<avolites.macros xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:noNamespaceSchemaLocation="Avolites.Menus.xsd">
  <macro id="Avolites.Macros.ReleaseLists" name="Release Lists">
    <description>Releases some playbacks.</description>
    <sequence>
      <step>Playbacks.ReleasePlayback(userNumber:83,
Playbacks.MasterReleaseTime, true)</step>
      <step>Playbacks.ReleasePlayback(userNumber:2,
Playbacks.MasterReleaseTime, true)</step>
      <step>Playbacks.ReleasePlayback(userNumber:79,
Playbacks.MasterReleaseTime, true)</step>
      <step>Playbacks.ReleasePlayback(userNumber:3,
Playbacks.MasterReleaseTime, true)</step>
      <step>Playbacks.ReleasePlayback(userNumber:4,
Playbacks.MasterReleaseTime, true)</step>
      <step>Playbacks.ReleasePlayback(userNumber:81,
Playbacks.MasterReleaseTime, true)</step>
      <step>Playbacks.ReleasePlayback(userNumber:50,
Playbacks.MasterReleaseTime, true)</step>
    </sequence>
  </macro>

  <macro id="Avolites.Macros.FirePlayback83" name="Fire Hold">
```

```
<description>Fire Hold State.</description>
<sequence>
  <step>Playbacks.FirePlaybackAtLevel(userNumber:83, level:1,
true)</step>
</sequence>
</macro>

<macro id="Avolites.Macros.ReleasePlayback83" name="Release Hold">
  <description>Releases hold state.</description>
  <sequence>
    <step>Playbacks.ReleasePlayback(userNumber:83,
Playbacks.MasterReleaseTime, true)</step>
  </sequence>
</macro>
</avolites.macros>
```

## Explanation

This explains the functional steps within the sequence. For all the other XML details please refer to [Formats and syntax](#)

These macros are designed to work with specific usernumbers - either you adjust the usernumbers in the macro or you assign your playbacks the correct usernumbers.

`Playbacks.ReleasePlayback()` releases a certain playback in a given time - which here is taken from the property `Playbacks.MasterReleaseTime`.

`Playbacks.FirePlaybackAtLevel` fires a certain playback at a certain level.

Here, the playbacks are identifies by their [usernumber](#). Also note the syntax of defining the [level](#).

## How to use it

1. [make this macro available](#)
2. These macros are designed to work with specific usernumbers - either you adjust the usernumbers in the macro or you assign your playbacks the correct usernumbers.

From:  
<https://avosupport.de/wiki/> - **AVOSUPPORT**

Permanent link:  
<https://avosupport.de/wiki/macros/example/firereleaseplayback?rev=1511858912>

Last update: **2017/11/28 08:48**

