

Example

Nudge Master Up/Down

| | |
|---------------------|---|
| by: | Alberto Faria Costa, May 2018 |
| published: | http://forum.avolites.com/viewtopic.php?f=3&p=20557 |
| description: | Macros to nudge a master up/down |

[nudge](#), [master](#)

functions

- [Masters.NudgeUp](#)
- [Masters.NudgeDown](#)

For the available master's handleIds see [titanId](#)

Code

[nudgeratemaster.xml](#)

```
<?xml version="1.0" encoding="utf-8"?>
<avolites.macros xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:noNamespaceSchemaLocation="Avolites.Menus.xsd">

  <!-- RATE MASTERS -->
  <!-- Rate Grand Master: titanid=1604 -->
  <!-- Rate Master 1: titanid=1608 -->
  <!-- Rate Master 2: titanid=1612 -->
  <!-- Rate Master 3: titanid=1616 -->
  <!-- Rate Master 4: titanid=1620 -->
  <!-- http://www.avolites.de/wiki/macros:types:object:handle:titanid -->
  <!-- Created by: Alberto Faria Costa -->

  <macro id="Avolites.Macros.RateMasterNudgeUp" name="RATE MASTER UP">
    <sequence>
      <step>Masters.NudgeUp(1604)</step>
    </sequence>
  </macro>

  <macro id="Avolites.Macros.RateMasterNudgeDown" name="RATE MASTER
DOWN">
    <sequence>
      <step>Masters.NudgeDown(1604)</step>
    </sequence>
  </macro>
```

```
<!-- add macros for the other masters here ... -->  
  
</avolites.macros>
```

Explanation

This explains the functional steps within the sequence. For all the other XML details please refer to [Formats and syntax](#)

The functions `Masters.NudgeUp()` and `Masters.NudgeDown()` are called for a specific master, identified by its titanId.

How to use it

- [make this macro available](#)

tbd

From: <https://avosupport.de/wiki/> - **AVOSUPPORT**

Permanent link: <https://avosupport.de/wiki/macros/example/nudgemaster?rev=1537103151>

Last update: **2018/09/16 13:05**

