

Example

# Patch - Park fixtures 1 thru 100000

|                     |   |
|---------------------|---|
| <b>by:</b>          | Sebastian Beutel, July 2020   |
| <b>idea:</b>        | Yenz Nyholm, see<br><a href="https://www.facebook.com/groups/Avolites/permalink/1931175330348025/">https://www.facebook.com/groups/Avolites/permalink/1931175330348025/</a> |
| <b>description:</b> | Parks/unparks fixtures 1 ~ 100000   |

[park, fixtures](#)

## functions

- [Menu.Stack.PushOrReloadMenu](#)
- [Menu.InjectInput](#)
- [Programmer.Editor.Selection.GetSelectedHandles](#)
- [Handles.SetSourceHandleRangeFromHandles](#)
- [Patch.Repatch.SetDmxAddressesFromSelectedFixture](#)
- [Patch.Repatch.ParkSelectedFixtures](#)
- [Patch.Repatch.UnParkSelectedFixtures](#)
- [Handles.ClearSelection](#)
- [Programmer.Editor.ClearAll](#)

## affected properties

- [Windows.PatchView.Handles](#)
- [Patch.Repatch.SelectedFixtureHandles](#)

The repatch menu does not actually use the PatchSelection, it has its own property Patch.Repatch.SelectedFixtureHandles.

## Code

[ParkFixtures1Thru100000.xml](#)

```
<?xml version="1.0" encoding="utf-8" ?>
<avolites.macros>

<!--
  Sebastian Beutel, July 2020
  idea by Yenz Nyholm
  see
  https://www.facebook.com/groups/Avolites/permalink/1931175330348025/
-->

<macro id="Avolites.Macros.ParkFixturesOneThru100000" name="Park
Fixtures 1 Thru 100000">
```

```
<description>Parks fixtures 1 ~ 100000.</description>
<sequence>
  <step pause="0.001">Menu.Stack.PushOrReloadMenu("Primary",
"Expert.Root.Program")</step>
  <step
pause="0.001">Menu.InjectInput("OnButtonDown", "Channel", "", 0)</step>
  <step
pause="0.001">Menu.InjectInput("OnButtonDown", "NumericKeys", "", 1)</step>
>
  <step
pause="0.001">Menu.InjectInput("OnButtonDown", "KeypadThrough", "", 0)</st
ep>
  <step
pause="0.001">Menu.InjectInput("OnButtonDown", "NumericKeys", "", 1)</step>
>
  <step
pause="0.001">Menu.InjectInput("OnButtonDown", "NumericKeys", "", 0)</step>
>
  <step
pause="0.001">Menu.InjectInput("OnButtonDown", "NumericKeys", "", 0)</step>
>
  <step
pause="0.001">Menu.InjectInput("OnButtonDown", "NumericKeys", "", 0)</step>
>
  <step
pause="0.001">Menu.InjectInput("OnButtonDown", "KeypadEnter", "", 0)</step>
>
  <step
pause="0.01">Programmer.Editor.Selection.GetSelectedHandles("Windows.Pa
tchView.Handles")</step>
  <step
pause="0.01">Handles.SetSourceHandleRangeFromHandles(Windows.PatchView.
Handles, true)</step>
  <step
pause="0.01">Patch.Repatch.SetDmxAddressesFromSelectedFixture()</step>
  <step pause="0.01">Patch.Repatch.ParkSelectedFixtures()</step>
  <step pause="0.01">Handles.ClearSelection()</step>
  <step pause="0.01">Programmer.Editor.ClearAll()</step>
</sequence>
</macro>

<macro id="Avolites.Macros.UnparkFixturesOneThru100000" name="Unpark
Fixtures 1 Thru 100000">
```

```
<description>Unparks fixtures 1 ~ 100000.</description>
<sequence>
  <step pause="0.001">Menu.Stack.PushOrReloadMenu("Primary",
"Expert.Root.Program")</step>
  <step
pause="0.001">Menu.InjectInput("OnButtonDown", "Channel", "", 0)</step>
  <step
pause="0.001">Menu.InjectInput("OnButtonDown", "NumericKeys", "", 1)</step
>
  <step
pause="0.001">Menu.InjectInput("OnButtonDown", "KeypadThrough", "", 0)</st
ep>
  <step
pause="0.001">Menu.InjectInput("OnButtonDown", "NumericKeys", "", 1)</step
>
  <step
pause="0.001">Menu.InjectInput("OnButtonDown", "NumericKeys", "", 0)</step
>
  <step
pause="0.001">Menu.InjectInput("OnButtonDown", "NumericKeys", "", 0)</step
>
  <step
pause="0.001">Menu.InjectInput("OnButtonDown", "NumericKeys", "", 0)</step
>
  <step
pause="0.001">Menu.InjectInput("OnButtonDown", "NumericKeys", "", 0)</step
>
  <step
pause="0.001">Menu.InjectInput("OnButtonDown", "KeypadEnter", "", 0)</step
>
  <step
pause="0.01">Programmer.Editor.Selection.GetSelectedHandles("Windows.Pa
tchView.Handles")</step>
  <step
pause="0.01">Handles.SetSourceHandleRangeFromHandles(Windows.PatchView.
Handles, true)</step>
  <step
pause="0.01">Patch.Repatch.SetDmxAddressesFromSelectedFixture()</step>
  <step
pause="0.01">Patch.Repatch.UnParkSelectedFixtures(true)</step>
  <step pause="0.01">Handles.ClearSelection()</step>
  <step pause="0.01">Programmer.Editor.ClearAll()</step>
</sequence>
</macro>

</avolites.macros>
```

Here, the pause="0.01" seems to be required - if there is no pause, always the previously for repatching selected fixtures will be parked, and if there aren't any an exception is thrown.

## Explanation

This explains the functional steps within the sequence. For all the other XML details please refer to [Formats and syntax](#)

The first part simply emulates fixture selection by syntax, like `1 THRO 100000`:

- `Menu.Stack.PushOrReloadMenu("Primary", "Expert.Root.Program")` makes sure we are in the root menu
- the `Menu.InjectInput(. .)` commands emulate the button presses `Fixture 1 THRO 1 0 0 0 0 Enter`

This way the fixtures 1 ~ 100000 are selected.

The following code is taken from [Patch - Park selected fixtures](#)

- The first line retrieves the current selection and stores it in a menu property, it is not important which one just that it is the correct type.
- From that we then set the source handle selection (this is the same selection that is used for copy, move, set legend etc.).
- The third line copies the source handle selection to the Repatch property (and initialises other properties used in the repatch menu).
- The fourth line performs the Park operation and
- the last line clears the source handle selection once you are done.

## How to use it

- [make this macro available](#)
- When needed, select some fixtures and apply this macro in order to park these fixtures.

From: <https://avosupport.de/wiki/> - **AVOSUPPORT**

Permanent link: <https://avosupport.de/wiki/macros/example/parkfixtures1thru100000?rev=1594386776>

Last update: **2020/07/10 13:12**

