Example

# Perk/Restore/Swop Programmer

| | |
|---|---|
| **by:** | Sebastian Beutel, June 2018 |
| **published:** | here |
| **description:** | Emulate dual programmer:<br>- park programmer<br>- restore programmer<br>- swop programmer |

park, restore, swop, programmer

### functions

- Handles.SetSourceHandle
- Handles.ConfirmDelete
- ActionScript.SetProperty
- ActionScript.SetProperty.Enum
- Playbacks.StoreCue
- Programmer.Editor.Clear
- Handles.SetUserNumber
- Handles.SetLegend
- Handles.ClearSelection
- Include.SelectPlayback
- Handles.CopyDestination

### affected properties

- Expert.RecordPlayback.RecordMode.ModeOnEnter
- Playbacks.RecordMode
- Handles.CurrentUserNumber
- Handles.PendingLegend
- Handles.OperationMode

## Code

PrkRestoreProgrammer.xml

```
<?xml version="1.0" encoding="utf-8"?>
<avolites.macros>
<!-- Macros to emulate a second programmer - you can store the current programmer,
     retrieve it again, and swop between the current and the stored programmer -->
<!-- As Playbacks.StoreCue() always writes on the current page in the refererenced handle group,
     I chose the Macro window to store these special playbacks. -->
```

```
<!-- Sebastian Beutel, 27-06-2018 -->

  <!-- Store programmer into a cue -->
  <macro id="SB.Macros.Programmer.Park" name="SB Park Programmer">
    <description>Park Programmer to a playback</description>
    <sequence>
      <!-- store current programmer to playback #1000 -->
      <step>Handles.SetSourceHandle("Macros", 1000)</step>
      <step>Handles.ConfirmDelete()</step>
<step>ActionScript.SetProperty("Expert.RecordPlayback.RecordMode.ModeOn
Enter", Playbacks.RecordMode)</step>
      <step>ActionScript.SetProperty.Enum("Playbacks.RecordMode",
"RecordCueModeProgrammer")</step>
      <step>Playbacks.StoreCue("Macros", 1000, false)</step>
      <step>Programmer.Editor.Clear(255, true, false, 0)</step>
      <step>ActionScript.SetProperty("Playbacks.RecordMode",
Expert.RecordPlayback.RecordMode.ModeOnEnter)</step>

      <!-- set usernumber and legend -->
      <step>Handles.SetSourceHandle("Macros", 1000)</step>
      <step>ActionScript.SetProperty("Handles.CurrentUserNumber",
userNumber:10000)</step>
      <step>Handles.SetUserNumber()</step>
      <step>ActionScript.SetProperty("Handles.PendingLegend", "Parked
Programmer")</step>
      <step>Handles.SetLegend()</step>
      <step>Handles.ClearSelection()</step>
    </sequence>
  </macro>

  <!-- Retrieve programmer from a cue -->
  <macro id="SB.Macros.Programmer.Restore" name="SB Restore
Programmer">
    <description>Restore Programmer from a playback</description>
    <sequence>
      <step>Programmer.Editor.Clear(255, true, false, 0)</step>
      <step>Include.SelectPlayback("Macros", 1000)</step>
    </sequence>
  </macro>

  <!-- Swop programmer with previously parked programmer -->
  <macro id="SB.Macros.Programmer.Swop" name="SB Swop Programmer">
    <description>Swop programmer with previously parked
programmer</description>
    <sequence>
      <!-- store current programmer to playback #1001 -->
      <step>Handles.SetSourceHandle("Macros", 1001)</step>
      <step>Handles.ConfirmDelete()</step>
<step>ActionScript.SetProperty("Expert.RecordPlayback.RecordMode.ModeOn
Enter", Playbacks.RecordMode)</step>
```

```
      <step>ActionScript.SetProperty.Enum("Playbacks.RecordMode",
"RecordCueModeProgrammer")</step>
      <step>Playbacks.StoreCue("Macros", 1001, false)</step>
      <step>ActionScript.SetProperty("Playbacks.RecordMode",
Expert.RecordPlayback.RecordMode.ModeOnEnter)</step>

      <!-- load previous programmer from playback #1000 -->
      <step>Programmer.Editor.Clear(255, true, false, 0)</step>
      <step>Include.SelectPlayback("Macros", 1000)</step>

      <!-- delete playback #1000, move playback #1001 to #1000 -->
      <step>Handles.SetSourceHandle("Macros", 1000)</step>
      <step>Handles.ConfirmDelete()</step>
      <step>Handles.SetSourceHandle("Macros", 1001)</step>
      <step>ActionScript.SetProperty.Enum("Handles.OperationMode",
"move")</step>
      <step>Handles.CopyDestination("Macros", 1000)</step>
      <step>Handles.ClearSelection()</step>

      <!-- set usernumber and legend -->
      <step>Handles.SetSourceHandle("Macros", 1000)</step>
      <step>ActionScript.SetProperty("Handles.CurrentUserNumber",
userNumber:10000)</step>
      <step>Handles.SetUserNumber()</step>
      <step>ActionScript.SetProperty("Handles.PendingLegend", "Parked
Programmer")</step>
      <step>Handles.SetLegend()</step>
      <step>Handles.ClearSelection()</step>

    </sequence>
  </macro>
</avolites.macros>
```

## Explanation

This explains the functional steps within the sequence. For all the other XML details please refer to Formats and syntax

tbd

## How to use it

1. make this macro available

tbd

From:
https://avosupport.de/wiki/ - **AVOSUPPORT**

Permanent link:
**https://avosupport.de/wiki/macros/example/parkprogrammer?rev=1537114064**

Last update: **2018/09/16 16:07**