

Example

Fan - Parts

by:	Alex del Bondio, January 2019
published:	http://forum.avolites.com/viewtopic.php?f=20&t=5962#p21516
description:	Set fan parts to various values
remarks:	

[fan](#), [parts](#), [active](#), [binding](#), [converter](#)

functions

- [ActionScript.SetProperty](#)
- [Math.EnumAsStringEqualityConverter](#)

affected properties

- [Programmer.Editor.Fixtures.Fan.SegmentCount](#)

specials

- [Active Binding](#)

Code

[setfanparts.xml](#)

```
<?xml version="1.0" encoding="utf-8"?>
<avolites.macros>

  <macro id="Macros.FanParts.1" name="Set Fan In 1 Part">
    <active binding="{propertyLink
id='Programmer.Editor.Fixtures.Fan.SegmentCount'
converter='Math.EnumAsStringEqualityConverter'
converterParameter='1'}"/>
    <sequence>
<step>ActionScript.SetProperty("Programmer.Editor.Fixtures.Fan.SegmentC
ount",1)</step>
    </sequence>
  </macro>

  <macro id="Macros.FanParts.2" name="Set Fan In 2 Part">
    <active binding="{propertyLink
id='Programmer.Editor.Fixtures.Fan.SegmentCount'
converter='Math.EnumAsStringEqualityConverter'
converterParameter='2'}"/>
```

```
<sequence>  
<step>ActionScript.SetProperty("Programmer.Editor.Fixtures.Fan.SegmentC  
ount",2)</step>  
</sequence>  
</macro>  
  
</avolites.macros>
```

Explanation

This explains the functional steps within the sequence. For all the other XML details please refer to [Formats and syntax](#)

The macros set the fan parts to various values. They also show the current value using [Active Binding](#)

How to use it

- [make this macro available](#)
- copy the macros on buttons for easy access

From:
<https://avosupport.de/wiki/> - **AVOSUPPORT**

Permanent link:
<https://avosupport.de/wiki/macros/example/setfanparts>

Last update: **2019/05/05 12:00**

