

Example

Legend - Set a playback's legend

by:	Kim Wida/Gregory Haynes, Feb 2018
published:	http://forum.avolites.com/viewtopic.php?f=20&t=5576
description:	Set a playback's legend
remarks:	

[playback](#), [legend](#)

functions

- [Handles.SetSourceHandleFromHandle](#)
- [ActionScript.SetProperty](#)
- [Handles.SetLegend](#)
- [Handles.ClearSelection](#)

properties

- [Handles.SourceHandle](#) (*Implicitly used.*)
- [Handles.PendingLegend](#)

Code

[setPlaybackLegend.xml](#)

```
<?xml version="1.0" encoding="utf-8"?>
<avolites.macros>
  <macro name="Set Chase 10555 legend" id="Macros.SetChaseLegend">
    <description></description>
    <sequence>
      <step>Handles.SetSourceHandleFromHandle("chaseHandleUN=10555")</step>
      <step>ActionScript.SetProperty("Handles.PendingLegend",
"Test")</step>
      <step>Handles.SetLegend()</step>
      <step>Handles.ClearSelection()</step>
    </sequence>
  </macro>
</avolites.macros>
```

Explanation

This explains the functional steps within the sequence. For all the other XML details please refer to

Formats and syntax

This is an example of how to set a playback's legend. (There is another example for [setting a playback cue's legend](#)).

- `Handles.SetSourceHandleFromHandle("chaseHandleUN=10555")` selects a specific handle to set its legend.
- `ActionScript.SetProperty("Handles.PendingLegend", "Test")` sets the general property 'Handles.PendingLegend' to a specific string
- `Handles.SetLegend()` applies this legend to the previously selected playback
- `Handles.ClearSelection()` unselects the playback handle.

How to use it

1. edit to meet your needs (or set a chaser to userNumber 10555) and [make this macro available](#)
2. call this macro to set this playback's legend. Most likely you will use this for other purposes.

From:
<https://avosupport.de/wiki/> - **AVOSUPPORT**

Permanent link:
<https://avosupport.de/wiki/macros/example/setplaybacklegend?rev=1556364595>

Last update: **2019/04/27 11:29**

