

Example

## Playback - Set key profile

<b>by:</b>	Kim Wida, Feb 2018
<b>published:</b>	<a href="http://forum.avolites.com/viewtopic.php?f=20&amp;t=5553">http://forum.avolites.com/viewtopic.php?f=20&amp;t=5553</a>
<b>description:</b>	Set a playback's key profile
<b>remarks:</b>	see also <a href="http://forum.avolites.com/viewtopic.php?f=20&amp;t=5580">http://forum.avolites.com/viewtopic.php?f=20&amp;t=5580</a>

[playback](#), [profile](#)

### functions

- [Profiles.AssignHandleProfile](#)
- [Profiles.GetHandleProfileId](#)

### identifiers

- [profileId](#)

## Code

[setProfile.xml](#)

```
<?xml version="1.0" encoding="utf-8"?>
<avolites.macros xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:noNamespaceSchemaLocation="Avolites.Menus.xsd">
  <macro name="Set Key Profile to UN11047"
id="Wiki.Macros.SetplaybackProfile">
    <sequence>
      <step>Profiles.AssignHandleProfile(handle:"chaseHandleUN=10555",
Profiles.GetHandleProfileId(handle:"chaseHandleUN=11047"))</step>
    </sequence>
  </macro>

  <macro name="Set Key Profile of chaser 5563"
id="Wiki.Macros.SetplaybackProfile.Ex1">
    <sequence>
<step>Profiles.AssignHandleProfile(handle:"chaseHandleUN=5963",493461)<
/step>
    </sequence>
  </macro>

</avolites.macros>
```

## Explanation

This explains the functional steps within the sequence. For all the other XML details please refer to [Formats and syntax](#)

As the [Profile IDs](#) of user-defined key profiles are random, the first example might be much more useful than the second: it sets the key profile of one playback to the key profile of another playback:

- `Profiles.GetHandleProfileId(handle:"chaseHandleUN=11047")` retrieves the profile id of the playback with user number 11047.
- `Profiles.AssignHandleProfile(handle:"chaseHandleUN=10555", ...)` assigns this as profile id for another playback

The second example directly sets a profile id - however, as the correct ID cannot be predicted, you'd need to find the correct id e.g. with [this example](#) and manually enter the number in the macro - not very handy.

## How to use it

1. [make this macro available](#)
2. create a chaser with #11047 as dummy playback and set its key profile.
3. in order to apply this to another chaser re-legend that other chaser to #10555 and fire the macro

The second macro is merely for documentation purposes - you'd need to edit it to match the profile id of your show.

From:  
<https://avosupport.de/wiki/> - **AVOSUPPORT**

Permanent link:  
<https://avosupport.de/wiki/macros/example/setplaybackprofile>

Last update: **2019/04/27 15:07**

