

Example

Timecode - Set starttime to livetime and toggle source

by:	Roger Pique
published:	April 2020
description:	Sets Timecode 1 to TimecodeOne Live Time.
remarks:	Useful for timecode shows where you temporarily need to disconnect from timecode without killing all playbacks, and be able to resume timecode operation later. See detailed description below.

[timecode](#), [time](#), [live](#), [source](#)

functions

- [someusedfunction](#)
- [anotherusedfunction](#)
- [someusedfunction](#)
- [anotherusedfunction](#)

affected properties

- [someproperty](#)
- [anotherusedproperty](#)

control structures

- [step condition](#)

Code

[filename.xml](#)

```
<?xml version="1.0" encoding="utf-8"?>
<avolites.macros>

  <macro id="Wiki.Macros.SetTimecodeOneLiveTime"
name="SetTimecodeOneLiveTime">
  <description>Sets Timecode 1 to TimecodeOne Live
Time.</description>
  <sequence>
<step>Timecode.TimecodeOne.SetStartTime(Timecode.AsObservable(Timecode.
TimecodeOne.LiveTime))</step>
  <step
condition="Math.IsEqual(Timecode.TimecodeOne.IsControlAllowed,
```

```
true)">Timecode.TimecodeOne.Reset()</step>  
<step>ActionScript.SetProperty.Enum("Timecode.TimecodeOne.Source",  
"Internal")</step>  
<step>Timecode.TimecodeOne.SetSource(Timecode.TimecodeOne.Source)</step>  
>  
    </sequence>  
</macro>  
</avolites.macros>
```

Explanation

This explains the functional steps within the sequence. For all the other XML details please refer to [Formats and syntax](#)

tbd

How to use it

1. [make this macro available](#)

tbd

From:
<https://avosupport.de/wiki/> - **AVOSUPPORT**

Permanent link:
<https://avosupport.de/wiki/macros/example/timecodelivetime?rev=1723215432>

Last update: **2024/08/09 14:57**

