

Example

Timecode - Winamp Tracks

| | |
|---------------------|---|
| by: | Sebastian Beutel, November 2019 |
| published: | here |
| description: | example to fire some distinct Winamp tracks based on the actual time |
| remarks: | idea: https://www.facebook.com/groups/1811437589141428/permalink/2489876031297577/ timecode, winamp, track, fire |

The idea is to fire some Winamp tracks - with a timecoded show per track - at various times (real time of day).

The first idea to put everything into one cue list did not work as then the timecode stamps would not be in successive order. However it can be done with two separate cue lists which also has some more advantages, e.g. it is very easy to adjust the general showtime (just offset the times in the Masterlist) without tampering with the showlist's times.

In theory it would be possible to do this without any coded macros by using the Winamp fixture but this turns out to be not very reliable (see [Alex Del Bondio's remarks](#)). Thus, Winamp is assigned as timecode source, and the tracks are selected with `SetStartTime()`.

Global parameters:

- Timecode 2 is set to Winamp (for additional safety this is done every time a track is fired)
- Timecode 3 is set to Clock
- the master cue list needs to be set to Timecode source = Clock (playback options)
- the show cue list needs to be set to Timecode source = Winamp (playback options)
- Of course the timer needs to be enabled and proper timestamps be defined

[A macro file with track macros for track 1~4 and the pause macro is available here:](#)

timecodespecial.xml

functions

- [ActionScript.SetProperty.Enum](#)
- [Timecode.TimecodeX.SetSource](#)
- [Timecode.TimecodeX.SetStartTime](#)
- [Timecode.MakeTimecodeTime](#)
- [Math.IsEqual](#)
- [Timecode.TimecodeX.Reset](#)
- [Timecode.TimecodeX.Play](#)
- [Timecode.TimecodeX.Pause](#)

affected properties

- [Timecode.TimecodeX.Source](#)
- [Timecode.TimecodeX.IsControlAllowed](#)

control structures

- [condition](#)
- [Step Pause](#)

Code

filename.xml

```
<?xml version="1.0" encoding="utf-8"?>
<avolites.macros xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:noNamespaceSchemaLocation="Avolites.Menus.xsd">
  <macro name="" id="">
    <description></description>
    <sequence>
      <step></step>
    </sequence>
  </macro>
</avolites.macros>
```

Explanation

This explains the functional steps within the sequence. For all the other XML details please refer to [Formats and syntax](#)

tbd

How to use it

1. [make this macro available](#)

tbd

From:
<https://avosupport.de/wiki/> - **AVOSUPPORT**

Permanent link:
<https://avosupport.de/wiki/macros/example/timecodetracks?rev=1574071987>

Last update: **2019/11/18 10:13**

