Example

Timeline: Import Markers

by:	Sebastian Beutel with massive help from GRegory Haynes, March 2023
published:	here
description:	Import a marker file into a designated timeline
remarks:	from the facebook group: https://www.facebook.com/groups/Avolites/posts/2787203324745217/

timeline, import, marker

functions

- Timelines.ImportMarkersFromString
- Handles.GetTitanIdFromHandle
- Timecode.ParseFrameRate

Code

ImportMarkerMacros.xml

```
<?xml version="1.0" encoding="utf-8"?>
<avolites.macros>
  <macro id="Wiki.Macros.Timeline.ImportMarkers" name="Import Markers
TL 1">
    <sequence>
      <step>Timelines.ImportMarkersFromString(
        Handles.GetTitanIdFromHandle("timelineHandleUN=1"),
        "&lt;Version /&gt;",
        "C:\Users\sb\Documents\Titan\Markers\test.csv",
        Timecode.ParseFrameRate(100))
      </step>
    </sequence>
  </macro>
</avolites.macros>
```

Explanation

This explains the functional steps within the sequence. For all the other XML details please refer to Formats and syntax

Essentially it is just calling `Timelines.ImportMarkersFromString()` with the correct arguments (see Timelines.ImportMarkersFromString for other solutions):

1. `Handles.GetTitanIdFromHandle("timelineHandleUN=1")` is used to get the TitanId

from a specific usernumber as the function needs the titanId and not a handle
2. “`<Version />`” is the absolute minimum string as importMappingVersion

How to use it

1. make this macro available

tbd

From:
https://avosupport.de/wiki/ - **AVOSUPPORT**

Permanent link:
https://avosupport.de/wiki/macros/example/timelinemarkers?rev=1680508883

Last update: **2023/04/03 08:01**