ActionScript.SetProperty.Boolean

```
Void ActionScript.SetProperty.Boolean(String id, Boolean value)
```

API	http://api.avolites.com/10.1/ActionScript.SetProperty.Boolean.html
description	Sets an action script property to a boolean value.
Namespaces	ActionScript.SetProperty
parameter	id (String) : The id of the property.
	value (Boolean) : The value to set.
return value	(Void)

Example in

timecodeonoff:

```
ActionScript.SetProperty.Boolean("Timecode.Enabled", true)
```

Also used in

- Programmer - Align Fixtures
- Trigger - Toggle Audio Triggers On/Off
- Blind Mode On/Off
- Capture - Diagnostics
- Capture - Rendering Settings
- Change Pages with Timecode
- ColourChaseChanger (V2)
- Create Dummy Palettes
- Cuelist - Set Option FireFirstCue
- Delete Workspace X
- Off/On Attribute in Palette
- PaletteChaseChanger (V3)
- Shapes - Reverse All Shapes
- Shapes - Reverse, Offset, Restart
- Select all running shapes
- Set All Shapes Direction
- Set Lee Colour
- Set Playback's Shape Spread
- Timecode - Enable/Disable
- Function list
- String

Remarks

From:
https://avosupport.de/wiki/ - **AVOSUPPORT**

Permanent link:
https://avosupport.de/wiki/macros/function/actionscript.setproperty.boolean?rev=1509294871

Last update: **2017/10/29 16:34**