

Function

# Handles.GetHandle

```
Handle Handles.GetHandle(String group, Int32 page, Int32 index)
```

<b>API</b>	<a href="http://api.avolites.com/11.0/Handles.GetHandle.html">http://api.avolites.com/11.0/Handles.GetHandle.html</a>
<b>description</b>	Get the Handle currently occupying a slot
<b>namespace</b>	Handles
<b>parameter</b>	group( <a href="#">String</a> ) : Group name
	page ( <a href="#">Int32</a> ) : Page on that group
	index ( <a href="#">Int32</a> ) : Index on that page
<b>return value</b>	<a href="#">Handle</a>

## Example in

[setcuelistcuelegend](#):

```
Handles.GetHandle("PlaybackWindow", 0, 76)
```

Essentially this works similar to "Location=PlaybackWindow,0,76" where a handle is required, see Gregory's reply at <http://forum.avolites.com/viewtopic.php?f=20&t=5662#p20445>

## Also used in

- [Delete Playback](#)
- [Legend - Get a cuelist cue's legend](#)

## Remarks

From:  
<https://avosupport.de/wiki/> - **AVOSUPPORT**

Permanent link:  
<https://avosupport.de/wiki/macros/function/handles.gethandle?rev=1536423690>

Last update: **2018/09/08 16:21**

