

Function

# Handles.SetLockState

```
Void Handles.SetLockState(LockStates state)
```

|                     |                                                                                                                             |
|---------------------|-----------------------------------------------------------------------------------------------------------------------------|
| <b>API</b>          | <a href="http://api.avolites.com/11.0/Handles.SetLockState.html">http://api.avolites.com/11.0/Handles.SetLockState.html</a> |
| <b>description</b>  | Set the lock state of a handle                                                                                              |
| <b>namespace</b>    | Handles                                                                                                                     |
| <b>parameter</b>    | state ( <a href="#">LockStates</a> ) : "Unlocked", "TransparentLocked" or "FullyLocked"                                     |
| <b>return value</b> | Void                                                                                                                        |
| <b>affects</b>      | <a href="#">Handles.SourceHandle</a>                                                                                        |

## Example in

### [Playback - Set lock state](#)

```
<step>Handles.SetSourceHandle("PlaybackWindow", 0)</step>  
<step>ActionScript.SetProperty.Enum("Handles.SourceHandle.LockState",  
"FullyLocked")</step>  
<step>Handles.SetLockState(Handles.SourceHandle.LockState)</step>
```

Puts a lock on handle #1 of the current playbacks page.

Please note that the function expects an enum passed. See [Playback - Set lock state](#) for examples how to do this.

## Also used in

- [Playback - Set lock state](#)
- [Function list](#)

From:  
<https://avosupport.de/wiki/> - **AVOSUPPORT**

Permanent link:  
<https://avosupport.de/wiki/macros/function/handles.setlockstate?rev=1545584424>

Last update: **2018/12/23 17:00**

