Function

Handles.SetSourceHandle

```
Void Handles.SetSourceHandle(String group, Int32 index)
```

API	http://api.avolites.com/10.1/Handles.SetSourceHandle.html
description	Set the source handle to a specific group and index. Updates the context info
namespace	Handles
parameter	group (String) : group of handles
	index (Int32) : number of playback in specified group
return value	Void
affects	Handles.SourceHandle

See Identifiers for available groups of handles.

This always refers to the current page of the group. In order to select a handle on any page see Handles.SetSourceHandleFromHandle

Example in

Timecode - Toggle On/Off for particular playback:

```
  <step>Handles.SetSourceHandle("Playbacks", 0)</step>
```

Sets source handle to be handle #1 of the current playbacks page.

Also used in

- Create Dummy Palettes
- Create Workspaces
- Delete Workspace X
- Change Playback Timings Grid
- Move (Copy) Handle
- Store cues with current page names as legends
- Programmer - Park/Restore/Swop
- Timecode - Toggle On/Off for particular playback
- Playback - Record and set userNumber
- Legend - Set an icon as legend
- Playback - Set fade-in time - modular
- Playback - Set fade-out time
- Playback - Set lock state
- Function list
- Handles.SetSourceHandleFromHandle
- Handles

Remarks

From:
https://avosupport.de/wiki/ - **AVOSUPPORT**

Permanent link:
https://avosupport.de/wiki/macros/function/handles.setsourcehandle

Last update: **2018/09/16 12:26**