# Handles.SetSourceHandle

```
Void Handles.SetSourceHandle(String group, Int32 index)
```

| | |
|---|---|
| **API** | http://api.avolites.com/10.1/Handles.SetSourceHandle.html |
| **description** | Set the source handle to a specific group and index. Updates the context info |
| **namespace** | Handles |
| **parameter** | group ( String ) : group of handles |
| | index ( Int32 ) : number of playback in specified group |
| **return value** | Void |
| **affects** | Handles.SourceHandle |

See Identifiers for available groups of handles.

#### Example in

Timecode - Toggle On/Off for particular playback:

```
  <step>Handles.SetSourceHandle("Playbacks", 0)</step>
```

Sets source handle to be handle #1 of the current playbacks page.

#### Also used in

- Create Dummy Palettes
- Create Workspaces
- Delete Workspace X
- Change Playback Timings Grid
- Move (Copy) Handle
- Store cues with current page names as legends
- Programmer - Park/Restore/Swop
- Timecode - Toggle On/Off for particular playback
- Playback - Record and set userNumber
- Legend - Set an icon as legend
- Playback - Set fade-in time - modular
- Playback - Set fade-out time
- Playback - Set lock state
- Function list
- Handles.SetSourceHandleFromHandle
- Handles

#### Remarks

From:
https://avosupport.de/wiki/ - **AVOSUPPORT**

Permanent link:
**https://avosupport.de/wiki/macros/function/handles.setsourcehandle?rev=1511105956**

Last update: **2017/11/19 15:39**