Function

Handles.SetSourceHandle

```
Void Handles.SetSourceHandle(String group, Int32 index)
```

API	http://api.avolites.com/10.1/Handles.SetSourceHandle.html
description	Set the source handle to a specific group and index. Updates the context info
namespace	Handles
parameter	group (String) : group of handles
	index (Int32) : number of playback in specified group
return value	Void
affects	Handles.SourceHandle

See Identifiers for available groups of handles.

Example in

Timecode - Toggle On/Off for particular playback:

```
  <step>Handles.SetSourceHandle("Playbacks", 0)</step>
```

Sets source handle to be handle #1 of the current playbacks page.

Also used in

- Create Dummy Palettes
- Create Workspaces
- Delete Workspace X
- Change Playback Timings Grid
- Move (Copy) Handle
- Store cues with current page names as legends
- Programmer - Park/Restore/Swop
- Timecode - Toggle On/Off for particular playback
- Playback - Record and set userNumber
- Legend - Set an icon as legend
- Playback - Set fade-in time - modular
- Playback - Set fade-out time
- Playback - Set lock state
- Function list
- Handles.SetSourceHandleFromHandle
- Handles

Remarks

From:
https://avosupport.de/wiki/ - **AVOSUPPORT**

Permanent link:
https://avosupport.de/wiki/macros/function/handles.setsourcehandle?rev=1511344875

Last update: **2017/11/22 10:01**