

Function

# Handles.SetSourceHandle

```
Void Handles.SetSourceHandle(String group, Int32 index)
```

<b>API</b>	<a href="http://api.avolites.com/10.1/Handles.SetSourceHandle.html">http://api.avolites.com/10.1/Handles.SetSourceHandle.html</a>
<b>description</b>	Set the source handle to a specific group and index. Updates the context info
<b>namespace</b>	Handles
<b>parameter</b>	group ( <a href="#">String</a> ) : group of handles index ( <a href="#">Int32</a> ) : number of playback in specified group
<b>return value</b>	<a href="#">Void</a>
<b>affects</b>	<a href="#">Handles.SourceHandle</a>

See [Identifiers](#) for available groups of handles.

## Example in

[Timecode - Toggle On/Off for particular playback:](#)

```
<step>Handles.SetSourceHandle("Playbacks", 0)</step>
```

Sets source handle to be handle #1 of the current playbacks page.

## Also used in

- [Create Dummy Palettes](#)
- [Create Workspaces](#)
- [Delete Workspace X](#)
- [Change Playback Timings Grid](#)
- [Move \(Copy\) Handle](#)
- [Store cues with current page names as legends](#)
- [Programmer - Park/Restore/Swop](#)
- [Timecode - Toggle On/Off for particular playback](#)
- [Playback - Record and set userNumber](#)
- [Legend - Set an icon as legend](#)
- [Playback - Set fade-in time - modular](#)
- [Playback - Set fade-out time](#)
- [Playback - Set lock state](#)
- [Function list](#)
- [Handles.SetSourceHandleFromHandle](#)
- [Handles](#)

## Remarks

Last update: 2017/11/22 10:01 macros:function:handles.setsourcehandle <https://avosupport.de/wiki/macros/function/handles.setsourcehandle?rev=1511344875>

---

From:  
<https://avosupport.de/wiki/> - **AVOSUPPORT**

Permanent link:  
<https://avosupport.de/wiki/macros/function/handles.setsourcehandle?rev=1511344875>

Last update: **2017/11/22 10:01**

