Function

Handles.SetSourceHandleRange

```
Void Handles.SetSourceHandleRange(String group, List`1 indexList)
```

API	http://api.avolites.com/11.0/Handles.SetSourceHandleRange.html
description	Set the source handle to a specific range of handles
namespace	Handles
parameter	group (String) : group of handles
	indexList (List`1) : list of handles in specified group
return value	Void
affects	Handles.SourceHandle, Handles.ContextHandles

See Identifiers for available groups of handles.

Example in

Create Workspaces:

```
  <step pause="0.001">Handles.SetSourceHandleRange("Workspaces", {0, 1, 2,
3, 4, 5, 6, 7, 8, 9, 10, 11})</step>
```

Sets source handle to be workspace handles 1-12 (the 12 visible workspace buttons in Titan.

Another application would be to select the first handle, then set the flag "`Handles.ThroughModifier`", and finally select the last handle

1. SetSourceHandleRange(handle group, index of first handle)
2. ActionScript.SetProperty.SetFlag("Handles.ThroughModifier", "Once")
3. SetSourceHandleRange(handle group, index of first handle)

See http://forum.avolites.com/viewtopic.php?f=20&t=5788:

```
Handles.SetSourceHandleRange("PlaybackWindow", {0})
ActionScript.SetProperty.SetFlag("Handles.ThroughModifier", "Once")
Handles.SetSourceHandleRange("PlaybackWindow", {60})
```

Also used in

- Create Workspaces
- Cuelist - Set Option FireFirstCue
- Playback Groups - Create and Add
- Function list
- Handles.ContextHandles
- Handles.ThroughModifier

Remarks

From:
https://avosupport.de/wiki/ - **AVOSUPPORT**

Permanent link:
https://avosupport.de/wiki/macros/function/handles.setsourcehandlerange

Last update: **2021/06/13 10:51**