

Function

# Playbacks.FillCueLegend

```
Void Playbacks.FillCueLegend(Handle handle, Single cueNumber, String propertyId)
```

<b>API</b>	<a href="http://api.avolites.com/11.0/Playbacks.FillCueLegend.html">http://api.avolites.com/11.0/Playbacks.FillCueLegend.html</a>
<b>description</b>	Gets the legend of a cue and puts it in a property.
<b>namespace</b>	<a href="#">Playbacks</a>
<b>parameter</b>	handle ( <a href="#">Handle</a> ) : The handle of the cuelist or chase.
	cueNumber ( <a href="#">Single</a> ) : The cue number.
	propertyId ( <a href="#">String</a> ) : The id of the property the legend shall be assigned to.
<b>return value</b>	<a href="#">Void</a>

## Example in

[Legend - Get a cuelist cue's legend:](#)

```
<step>Playbacks.FillCueLegend(  
    Handles.GetHandle("PlaybackWindow",0,76),  
    Math.Cast.ToSingle(CueLists.LiveCueNumber),  
    "Handles.PendingLegend"  
)</step>
```

This gets the legend of the current cue of the cuelist in page 1 slot 77 of the Playbacks window and puts it in the property 'Handles.PendingLegend' for future use.

## Also used in

- [Legend - Get a cuelist cue's legend](#)

## Remarks

From:  
<https://avosupport.de/wiki/> - **AVOSUPPORT**

Permanent link:  
<https://avosupport.de/wiki/macros/function/playbacks.fillcuelegend?rev=1536424275>

Last update: **2018/09/08 16:31**

