Types/Object/Handle

userNumber

Within Titan, each and every single item which you program has a number - simply an integer number, which you, within reason, can assign freely. In most cases, this is either not conciously used at all, or used in a user-specific system (e.g. group #1 might be the front truss or a specific group of fixtures...). The userNumber can be used to refer to a specific item. Unlike the titanId which is unique in a global scope (i.e. per show there can only be one item with a specific titanId), the userNumber is unique only in its context (e.g. fixtures, groups, palettes, playbacks, macros etc.): there can only be one fixture with the number 1 - any subsequently patched fixture will be given another userNumber. But there may also exist group 1, palette 1, or playback 1.

userNumber is a positive integer value.

Usually the userNumber is passed like this:

`userNumber:2`

`“chaseHandleUN=10555”`

`“playbackHandleUN=10555”`

Internally there is some parsing/'educated guessing' performed, depending from the very function the usernumber is sent to. There is a nice explanation in the forum here http://forum.avolites.com/viewtopic.php?f=20&t=5576:

> The text string should match the type of the handle you are wanting to access. So in theory you should use cueHandle, chaseHandle and cuelistHandle dependent on the type of playback you are using. In this case the user numbers are shared by all three types so will probably work however may have side effects in other cases. There is also a generic playbackHandle that can be used for all three types.

Technically, this syntax looks like https://docs.microsoft.com/en-us/dotnet/csharp/programming-guide/classes-and-structs/named-and-optional-arguments: you have to name the argument 'userNumber', and after a colon give the value.

ASSUMPTION

> > It is a reasonable assumption that AcwUserNumber also refers to userNumber, but in the context of the value being given in the appropriate menu.

used in

- Chase - Change a chaser's XFade
- Playback - Fire/Release Playbacks from Usernumber
- Playback - Record and set userNumber
- Set Playback Priority

- Group.QuickCreateGroup
- PlaybackGroups.SetCurrentPlaybackGroupFromUserNumber
- Handle
- Identifiers
- Handles.CurrentUserNumber
- Playbacks.Editor.Times.ChaseXFade
- AcwUserNumber

From:
https://avosupport.de/wiki/ - **AVOSUPPORT**

Permanent link:
https://avosupport.de/wiki/macros/identifier/usernumber?rev=1534519569

Last update: **2018/08/17 15:26**