

Titan Property

# Expert.RecordPlayback.RecordMode.ModeOnEnter

<b>API</b>	./.
<b>description</b>	can be used to store th current RecordMode
<b>Namespaces</b>	<a href="#">Expert.RecordPlayback.RecordMode</a>
<b>type</b>	<a href="#">Enum</a> (as it is a <a href="#">RecordMode</a> )

## example

```
<step>ActionScript.SetProperty("Expert.RecordPlayback.RecordMode.ModeOnEnter", Playbacks.RecordMode)</step>
<step>ActionScript.SetProperty.Enum("Playbacks.RecordMode", "RecordCueModeProgrammer")</step>
<step>Playbacks.StoreCue("Macros", 1000, false)</step>
<step>Programmer.Editor.Clear(255, true, false, 0)</step>
<step>ActionScript.SetProperty("Playbacks.RecordMode", Expert.RecordPlayback.RecordMode.ModeOnEnter)</step>
```

The current RecordMode ist stored. Then some actions are performed (the RecordMode set to something, etc.), and then the RecordMode is restored from this property.

## used in

- [Programmer - Park/Restore/Swop](#)

From:  
<https://www.avosupport.de/wiki/> - AVOSUPPORT

Permanent link:  
<https://www.avosupport.de/wiki/macros/property/expert.recordplayback.recordmode.modeonenter>

Last update: 2018/09/16 17:13

