

Web API Parameter

Boolean

Strictly this is not a parameter but a type a parameter might be. For a more in-depth discussion see [Boolean](#) in the Macros section.

Boolean parameters can only be either `true` or `false`, the notation is

`parameterName=true` or `parameterName=false`.

Example

In [playbacks_fireplaybackatlevel](#) the parameter `alwaysRefire` is a boolean.

`FirePlaybackAtLevel?handle_userNumber=2&level_level=0.9&alwaysRefire=true` refires LTP values.

`FirePlaybackAtLevel?handle_userNumber=2&level_level=0.9&alwaysRefire=false` does not refire LTP values.

Errors

`FirePlaybackAtLevel?handle_userNumber=2&level_level=0.9&alwaysRefire=tru` gives

“Error: Die Zeichenfolge wurde nicht als gültiger Boolean erkannt.” (no valid boolean detected in string)

Reason: a boolean value may only be `true` or `false`. Even a missing `e` invalidates it. The same is true if the value is missing altogether (`alwaysRefire=`).

`FirePlaybackAtLevel?handle_userNumber=2&level_level=0.9&alwaysRefire` results in

“Error: Der Objektverweis wurde nicht auf eine Objektinstanz festgelegt.” (no object referenced)

Reason: and the equal sign is missing and thus the parameter is not recognized.

`FirePlaybackAtLevel?handle_userNumber=2&level_level=0.9&alwaysRefir=true` throws

“Error: Die Sequenz enthält kein übereinstimmendes Element.” (no matching element).

Reason: wrong parameter name.

Used In

- [Parameters](#)
- [Palette/ApplyPalette](#)
- [Playbacks/FirePlaybackAtLevel](#)

From:

<https://avosupport.de/wiki/> - **AVOSUPPORT**

Permanent link:

<https://avosupport.de/wiki/webapi/parameters/boolean?rev=1587309762>

Last update: **2020/04/19 15:22**

