

Web API request

Masters/SetSpeed

Sets the speed of a speed master from the menu.

| | |
|------------------|--|
| API | https://api.avolites.com/12.0/Masters.SetSpeed.html |
| namespace | Masters |
| usage | http://[ip]:4430/titan/script/2/Masters/SetSpeed?handle={handle}&value={float} |
| example | http://localhost:4430/titan/script/2/Masters/SetSpeed?handle_titanId=1612&value=100 (link opens in new tab) |
| action | set BPM Master 1 to 100 BPM |
| parameter | Handle: the master to be set value (Float: the numeric speed value to set (see remarks)) |
| returns | nothing if successful error messages if the request failed |
| remarks | Using a usernumber will fail as masters don't have one. Either assign the master to a handle and use its location or use the reserved Titan ID, see titanId in the Macros section For BPM masters the value directly transfers to a BPM value. For rate masters, unlike Masters/SetMaster which uses a normalized value (1 == 100%), here the numeric value is directly interpreted value. value=10 sets a rate master to 10%. |

Used In

- [MIDI To Web](#)
- [Web-API requests](#)

From:

<https://www.avosupport.de/wiki/> - **AVOSUPPORT**



Permanent link:

https://www.avosupport.de/wiki/webapi/requests/masters_setspeed

Last update: **2020/04/19 15:32**